



DH10

EXTENSION HUB

- Multiple interfaces
- Support All New-generation Terminals
- Wired or Wireless



DH10 (Wireless Version) Specifications

OS	Linux	●
Processor	AP: Dual-core Cortex-A7	●
Wired Communication	Ethernet 10/100 Base - T	●
Wireless Communication	Wi-Fi 2.4G (AP/P2P)	●
Peripheral Ports	2 x Type-A, 1 x RS232, 1 x Type-C, 1 x RJ45, 1 x Reset slot Optional: 1 x Cashdrawer port, 1 x DC port	●
Power Supply	Input: 100~240V AC 50/60Hz Output: DC5.0 DC, 2A	●
Dimensions	95mm (L) x 75.9mm (W) x 23.6mm (H)	●
Weight	89g	●
Environment	Operating temperature: 0°C~40°C (32°F~104°F)	●
	Storage temperature: -20°C~60°C (-4°F~140°F)	
	Relative humidity: 5% ~ 95% (Non - condensing)	
Certifications	CE, CB	●



PT Putra Mandiri Informatika

JAKARTA
Sedayu Square Blok M 23-25, RT.1/RW.12, Cengkareng Barat,
Kecamatan Cengkareng, Kota Jakarta Barat, Daerah Khusus
Ibukota Jakarta

